



Flash Memory Summit

# Using Floating Gate and Replacement Gate Technologies to Address Diverse Storage Market Needs

Sanjay Subbarao, Shankar Natarajan, Yihua Zang  
Solidigm

# The New Paradigm of Solid-State Storage

\$8B+ Revenue\*

\*Solidigm + SK Revenue

3 NAND Factories

Global Organization,  
HQ in California

- Solid-State Innovation Since 1987




- Leadership in Enterprise, Cloud & Client
- Pace-setting innovation across Floating Gate & Charge Trap, TLC & QLC

# Executive Summary




Flash Memory Summit

Having access to both technologies can enable independent delivery of optimized QLC/PLC bit density at higher capacities and, at the same time, deliver competitive bit density and higher performance at lower TLC capacity in parallel




# Floating Gate vs. Replacement Gate Structure

## Floating Gate 3D NAND



- ✓ Discrete cell isolation minimizes risk of cross-cell interference: Clear advantage for QLC and PLC.
- ✓ Good charge retention.
- Higher resistance of polysilicon WLs requires tile architecture to reduce WL RC.



## Replacement Gate 3D NAND




- ✓ Lower resistance of metal WLs enables faster operation.
- Lateral charge diffusion in nitride (storage element) leads to data retention challenge.



# QLC Implementation: FG vs. RG





P. Kalavade, "Completing the memory and storage hierarchy," Intel Memory and Storage Day, 2019.



- ✓ A **4-16 algorithm** is implemented, leveraging the intrinsic immunity of FG cell to quick charge loss
- ✓ Data from First Pass is readable, minimizing the data storage in DRAM/SLC cache
- ✓ Each page of data is dispatched to the NAND only once, minimizing the channel I/O traffic
- ✓ Floating gate NAND cell has higher retention due to immunity to lateral charge diffusion. FG has higher RWB margin

- To compensate for quick charge loss, cells are placed close to their final  $V_T$  during the first pass
- A **16-16 algorithm coarse fine** is typically used which requires all four pages of data dispatched to NAND during **both** first pass and second pass
  - **Requires first pass data to be cached in DRAM/SLC cache**
- RG has higher rate of charge loss and lower retention

# Higher Bit Density With FG Technology




- FG technology delivers 15% higher bit density normalized by number of tiers
- This is significant, considering the quoted cost reduction from one generation in 3D NAND is about 18%
- FG technology can enable PLC, leading to an additional 25% bit density



# Challenge of Maintaining Small Die Capacity

- To tackle higher WL resistance issue, FG technology uses tile architecture to reduce WL RC to levels comparable to typical RG technology
- This makes it more challenging to maintain small die capacity with best bit density, even though FG has been using Circuit-under-Array (CuA) and Zero-Periphery since its first generation of 3D NAND
  - WL segmentation via string drivers result in higher CuA area
  - Tile architecture requires splitting periphery circuits into multiple smaller sections, resulting in higher CuA area.
- **RG technology is a better option to design small capacity dies needed for mobile and small SSDs**
  - Minimum FG die size is  $\sim 70\text{mm}^2$  (144layer) whereas minimum RG die size is  $\sim 40\text{mm}^2$  (176 layer) (state of art)



Intel 64-Tier TLC







Image courtesy of TechInsights

# Performance Comparison



Flash Memory Summit

- RG technology offers higher TLC performance, enabled by choice of smaller die (shorter BLs) and lower WL RC delay
  - State-of-the-art RG is ~18% faster than FG technology
- For QLC, the choice of program algorithm (4-16 vs 16-16) compensates for the higher WL RC delay of FG technology
  - FG is actually faster than RG






# Conclusion: Optimizing for Diverse Market Segments

Having access to both technologies can enable independent delivery of optimized QLC/PLC bit density at higher capacities and, at the same time, deliver competitive bit density and higher performance at lower TLC capacity in parallel

**FG: Lowest Cost per Bit**  
Best for High-Capacity QLC/PLC SSDs

**RG: High-Performance TLC**  
Best for Small capacity SSDs / Mobile



# Solidigm at Flash Memory Summit 2022



Find us at booth 509!

Tuesday	Wednesday	Thursday
<p><b>QLC Value With No Compromise</b> 8:30 a.m. • Ballroom B (Session DCTR-101-1)</p> <p><b>Keynote</b> 2:10 p.m. • Mission City Ballroom</p> <p><b>Unlocking a Next-Level User Experience in Client/Edge Storage With Software</b> 3:20 p.m. • Ballroom C (Session EDGE-102-1)</p>	<p><b>SSD Firmware Resilience: Approaches and Challenges to Protect Against Emerging Threats</b> 3:30 p.m. • Ballroom D (Session SECR-202-1)</p> <p><b>Using Floating Gate and Replacement Gate Technologies to Address Diverse Storage Market Needs</b> 3:30 p.m. • Ballroom A (Session SSDS-202-1)</p> <p><b>5 Reasons You Should Be Adopting QLC NAND SSDs in Your Data Center Now</b> 3:30 p.m. • Great America Ballroom K (Session SSDS-202-1)</p>	<p><b>Above the Average: A Thoughtful Approach to Client Performance Reporting</b> 8:30 a.m. • Great America Ballroom K (Session TEST-301-1)</p> <p><b>Client Usage: The Need for Speed Beyond High-QD Read</b> 9:45 a.m. • Great America Ballroom K (Session TEST-301-2)</p> <p><b>Expanding Your SSD Assessment Beyond 4 Corners to Make the Best Storage Choice</b> 3:10 p.m. • Great America Ballroom K (Session TEST-302-2)</p>

# Disclaimers

All product plans, roadmaps, specifications, and product descriptions are subject to change without notice.

Nothing herein is intended to create any express or implied warranty, including without limitation, the implied warranties of merchantability, fitness for a particular purpose, and non-infringement, or any warranty arising from course of performance, course of dealing, or usage in trade.

The products described in this document may contain design defects or errors known as “errata,” which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Contact your Solidigm representative or your distributor to obtain the latest specifications before placing your product order.

For copies of this document, documents that are referenced within, or other Solidigm literature, please contact your Solidigm representative.

All products, computer systems, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice.

Tests document performance of components on a particular test, in specific systems. Differences in hardware, software, or configuration will affect actual performance. Consult other sources of information to evaluate performance as you consider your purchase.

Performance results are based on testing as of dates shown in the configurations and may not reflect all publicly available updates. See configuration disclosure for details. No product or component can be absolutely secure.

Solidigm or Intel optimizations, for Solidigm or Intel compilers or other products, may not provide optimized performance to the same degree for non-Solidigm or Intel products. Solidigm or Intel technologies may require enabled hardware, software, or service activation.

Your costs and results may vary.

Solidigm does not control or audit third-party data. You should consult other sources to evaluate accuracy.

Some results have been estimated or simulated using internal Solidigm analysis or architecture simulation or modeling, and provided to you for information purposes only. Any differences in your system hardware, software or configuration may affect your actual performance.

© Solidigm. “Solidigm” is a trademark of SK hynix NAND Product Solutions Corp (d/b/a Solidigm). “Intel” is a registered trademark of Intel Corporation. Other names and brands may be claimed as the property of others.